SUPS 3

SUPS 3-9 (1 ~230 V)

Article number 5144035098

Product page https://www.speck-neos.medienreaktor-kunden.de/en/p/sups-3-9-1-230-v-5144035098



Description

Die Unterwasserpumpen zeichnen sich durch eine hohe Wirtschaftlichkeit, lange Lebensdauer und einen gekapselten Unterwassermotor aus. Alle medium berührten Teile sind aus Edelstahl.

Areas of use

Water supply. Irrigation. Fountain systems. Heat pumps. Rainwater harvesting

Material short text

SUPS 3-9. We.. 0.55 kW

Technical data

Hydraulic power

Flow rate	4 m³/h
Head (min.)	55 mWS
Operating pressure max.	25 bar

Motor & drive

Speed (max.)	2,800 min-1
Motor phases	1 ~
Degree of protection	IP 68
Insulation class	B

Electrics

Power input P_1 (max.)	0 kW
Power output P_2 (max.)	0.55 kW
Voltage (max.)	1~ 230 V ± 10 %
Frequency	50 Hz

Energy efficiency

Energy efficiency class	IE2

Operating conditions & water

Ambient temperature (min.)	30 ° C
Temperature min.	30 ° C

Dimensions & logistics

Product length	671 mm
Product width	0 mm
Product height	0 mm
Net weight	15.1 kg
Customs tariff number	84137029