SUPS 15

SUPS 15-21 (3 ~400V)

Article number 5144150217

Product page https://www.speck-neos.medienreaktor-kunden.de/en/p/sups-15-21-3-400v-5144150217



Description

Die Unterwasserpumpen zeichnen sich durch eine hohe Wirtschaftlichkeit, lange Lebensdauer und einen gekapselten Unterwassermotor aus. Alle medium berührten Teile sind aus Edelstahl.

Areas of use

Water supply. Irrigation. Fountain systems. Heat pumps. Rainwater harvesting

Material short text

SUPS 15-21. Dr.. 5.5 kW

Technical data

Hydraulic power

Flow rate	20 m³/h
Head (min.)	129 mWS
Operating pressure max.	25 bar

Motor & drive

Speed (max.)	2,800 min-1
Motor phases	3 ~
Degree of protection	IP 68
Insulation class	B

Electrics

Power input P_1 (max.)	0 kW
Power output P_2 (max.)	5.5 kW
Voltage (max.)	3~ 400 V ± 10 %
Frequency	50 Hz

Energy efficiency

Energy efficiency class	IE3

Operating conditions & water

Ambient temperature (min.)	30 ° C
Temperature min.	30 ° C

Dimensions & logistics

Product length	2,227 mm
Product width	0 mm
Product height	0 mm
Net weight	46.8 kg
Customs tariff number	84137029