SUPS 46

# SUPS 46-12 (3 ~400V)

Article number 5161460127

Product page https://www.speck-neos.medienreaktor-kunden.de/en/p/sups-46-12-3-400v-5161460127



## Description

Die Unterwasserpumpen zeichnen sich durch eine hohe Wirtschaftlichkeit, lange Lebensdauer und einen gekapselten Unterwassermotor aus. Alle medium berührten Teile sind aus Edelstahl.

## Areas of use

Water supply. Irrigation. Fountain systems. Heat pumps. Rainwater harvesting

## Material short text

SUPS 46-12. Dr.. 18.5 kW

## Technical data

### Hydraulic power

| | |
|---|---|
| Flow rate | 60 m³/h |
| Head (min.) | 165 mWS |
| Operating pressure max. | 25 bar |

### Motor & drive

| | |
|---|---|
| Speed (max.) | 2,800 min-1 |
| Motor phases | 3 ~ |
| Degree of protection | IP 68 |
| Insulation class | B |

### Electrics

| | |
|---|---|
| Power input $P_1$ (max.) | 0 kW |
| Power output $P_2$ (max.) | 18.5 kW |
| Voltage (max.) | 3~ 400 V ± 10 % |
| Frequency | 50 Hz |

### Energy efficiency

| | |
|---|---|
| Energy efficiency class | IE3 |

### Operating conditions & water

| | |
|---|---|
| Ambient temperature (min.) | 30 ° C |
| Temperature min. | 30 ° C |

## Dimensions & logistics

| | |
|---|---|
| Product length | 2,473 mm |
| Product width | 0 mm |
| Product height | 0 mm |
| Net weight | 100 kg |
| Customs tariff number | 84137029 |