ZIS

# ZIS 40/08 WES

Article number 6404008038

Product page https://www.speck-neos.medienreaktor-kunden.de/en/p/zis-40-08-wes-6404008038



## Description

The submersible pumps are used for rainwater harvesting, irrigation, and sprinkling. They are characterized by easy installation, minimal noise, and dry-run protection via a floating switch.

## Areas of use

Irrigation Irrigation Rainwater harvesting

## Version

Multi-stage submersible pump (cistern pump) made of corrosion-resistant stainless steel/plastic, motor with built-in thermal overload protection. Ready-to-connect with a 20 m cable and Schuko plug. Pump medium: Clear liquids that do not chemically or mechanically attack the pump materials.

## Material short text

ZIS 40/08 WES, 0,60 kW, mit Schwimmer

## Technical data

### Hydraulic power

| | |
|---|---|
| Flow rate | 4.8 m³/h |
| Head (min.) | 48 – 85 mWS |

### Motor & drive

| | |
|---|---|
| Speed (max.) | 2,800 min-1 |
| Motor phases | 1~ |
| Degree of protection | IP 68 |
| Insulation class | F |

### Electrics

| | |
|---|---|
| Power output $P_2$ (max.) | 0.6 kW |

| | |
|---|---|
| Voltage (max.) | 1~ 230 V ± 10 % |
| Input voltage | 230 V |
| Frequency | 50 Hz |
| Cable length | 20 m |

### Connections & piping

| | |
|---|---|
| Connection, discharge side | G 1 1/4 |

### Operating conditions & water

| | |
|---|---|
| Temperature min. | 35 ° C |

## Dimensions & logistics

| | |
|---|---|
| Net weight | 15 kg |
| Customs tariff number | 84137029 |