ZISMATIC

ZISMATIC 40/10 WE

Article number 6010401028

Product page https://www.speck-neos.medienreaktor-kunden.de/en/p/zismatic-40-10-we-6010401028



Description

The proven multi-stage submersible pump features a compact installation, integrated control system, and dry-run protection. This ensures convenient pump operation.

Areas of use

Irrigation Irrigation Rainwater harvesting

Version

Multi-stage submersible pump (cistern pump) made of corrosion-resistant stainless steel/plastic, including a check valve, pressure switch, and dry-run protection. The motor features built-in thermal overload protection. Ready-to-connect with a 15 m cable and Schuko plug. The pump includes a diaphragm reservoir with a nominal capacity of 0.1 l. Flow: Clear liquids that do not chemically or mechanically attack the pump materials.

Material short text

Zismatic 40/10 We. 0,9 kW

Technical data

Hydraulic power

Flow rate	4 m³/h
Head (min.)	63 mWS

Motor & drive

Speed (max.)	2,800 min-1
Motor phases	1~
Degree of protection	IP 68
Insulation class	F

Electrics

Power output P_2 (max.)	0.9 kW
Voltage (max.)	1~ 230 V ± 10 %
Input voltage	230 V
Frequency	50 Hz
Cable length	15 m

Connections & piping

Connection, discharge side	Rp 1

Operating conditions & water

Temperature min.	35 ° C

Dimensions & logistics

Net weight	12.4 kg
Customs tariff number	84137029