
BADU RESORT-AK

BADU Resort 40-AK

Article number 2195400157

Product page https://www.speck-neos.medienreaktor-kunden.de/en/p/badu-resort-40-ak-2195400157



Description

Saltwater-optimized circulation pumps with drive-pump separation. For longer service life in corrosive environments.

Areas of use

Thermal waters, thermal brine, hatcheries, aquariums, koi ponds, RAS systems, research centers, zoo enclosures, aquatic habitats, salting systems, and various problematic media after checking the components and concentrations. Note: Please always specify the intended media when ordering so that the pump's compatibility can be tested.

Version

The pump corresponds to the respective standard version – however, the seal chamber is not mounted directly on the A-side motor mount, but is structurally separated from the motor by an intermediate lantern and labyrinth disc. Any escaping fluid and crystallizing minerals or salts thus do not come into contact with the motor and bearings. This ensures a significantly longer operating time compared to standard pumps for the aforementioned applications. Special sealing materials are available upon request.

Material short text

BADU Resort 40-AK, 3~, 2,20kW, schwarz

Technical data

Hydraulic power

Flow rate	40 m³/h
Head (min.)	0 – 18.1 mWS
Operating pressure max.	0 bar

Motor & drive

Speed (max.)	2,840 min-1
Motor phases	3~
Degree of protection	IP 55

Insulation class	F

Electrics

Power input P_1 (max.)	2.55 kW
Power output P_2 (max.)	2.2 kW
Voltage (max.)	3~ Y/Δ 400/230 V
Frequency	50 Hz

Connections & piping

Connection, inlet / suction side	90 mm
Connection, discharge side	90 mm
Recommended suction line diameter	90 mm
Recommended discharge line diameter	90 mm

Operating conditions & water

Total salt concentration	0 g/l

Dimensions & logistics

Product length	843 mm
Product width	0 mm
Product height	0 mm
Customs tariff number	84137051