AQUACELL AE-T

AE-T 6-70

Article number 5610607611

Product page https://www.speck-neos.medienreaktor-kunden.de/en/p/ae-t-6-70-5610607611



Description

The fully automatic single-pump pressure booster systems are compact, quiet, and delivered fully wired and piped. All units feature fully automatic pump control without frequency control.

Areas of use

Drinking water supply Domestic water supply Air conditioning systems Irrigation and watering

Version

The systems are automatically switched on and off by a pressure transmitter located on the discharge side. An 8-liter diaphragm pressure accumulator is mounted in the discharge line as a control tank. Electronic dry-run protection is integrated. The speed is controlled by a frequency converter mounted on the motor, including an LED display and keypad. Bluetooth monitoring is available via a smartphone app. Plug-in ready with a 1.5-meter cable and plug; the AE-T comes with a cable without a plug. Flow: Clear, even moderately aggressive liquids that do not chemically or mechanically attack the pump materials. Flow: Clear, even moderately aggressive liquids that do not chemically or mechanically attack the pump materials.

Material short text

Aquacell AE-T 6-70, Dr.,f. Zulaufbetrieb

Technical data

Hydraulic power

Flow rate	6 m³/h
Head (min.)	53.025 – 67.301 mWS
Flow rate of standby pump	0 m³/h
Operating pressure max.	10 bar
Number of pumps	1 St

Motor & drive

Speed (max.)	2,850 min-1
Degree of protection	IP 55
Insulation class	F

Electrics

Power output P_2 (max.)	1.5 kW
Input voltage	400 V
Frequency	50 Hz
Cable length	1.5 m

Energy efficiency

Energy efficiency class	IE3

Connections & piping

Connection, inlet / suction side	1¼ Rp
Connection, discharge side	1¼ R

Operating conditions & water

Ambient temperature (min.)	40 ° C

Dimensions & logistics

Net weight	43 kg
Gross weight	58 kg
Customs tariff number	84798997