BADU JET PRIMAVERA

BADU JET Primavera mit weißer LED Fertigmontagesatz

Article number 2327800000
Product page https://www.speck-neos.medienreaktor-kunden.de/en/p/badu-jet-primavera-mit-weisser-led-fertigmontagesatz-2327800000



Description

Innovative technology for ambitious swimmers. With optimized performance.

Areas of use

For wall installation in all pool designs, as an attraction, for fitness, as a wave or bubble bath, or for underwater massage upon medical advice. Swimming without turning is possible even in small pools.

Version

A powerful BADU pump connected via a suction and pressure line draws water through a flush-mounted plastic housing and nozzle housing in the pool. A powerful jet of water is returned to the pool via two adjustable nozzles that can be swiveled 60° in all directions. A multitude of openings in the intake panel ensure extremely low intake flow.

Material short text

BJ Primavera, FMS, 3~, 4kW, LED_W

Technical data

Hydraulic power

Flow rate	85 m³/h

Motor & drive

Motor phases	3~
Degree of protection	IP X5
Insulation class	F

Electrics

Power input P_1 (max.)	4.55 kW
Power output P_2 (max.)	4 kW
Voltage (max.)	3 N~ Δ 400 V

Frequency	50 Hz

General / Product features

Product range	BADU Premium

Connections & piping

Recommended suction line diameter	75 mm
Recommended discharge line diameter	75 mm

Nozzles & counter-current system

Number of nozzles	2 St
Nozzle swivels in all directions	60 °
Outlet pressure at the nozzle	1 bar
Outlet velocity, centred 2 m in front of the nozzle	1.2 m/s
Massage pressure max.	1.8 bar

Operating conditions & water

Ambient temperature (min.)	40 ° C
Total salt concentration	0.066 %

Dimensions & logistics

Customs tariff number	84798997