BADU JET VOGUE DELUXE

# BADU JET Vogue Deluxe mit weißer LED Fertigmontagesatz

Article number 2324400000
Product page https://www.speck-neos.medienreaktor-kunden.de/en/p/badu-jet-vogue-deluxe-mit-weisser-led-fertigmontagesatz-2324400000



## Description

A material version of the BADU JET Vogue with a touch of luxury. Made entirely of stainless steel. And beyond reproach.

## Areas of use

For wall installation in all pool designs, as an attraction, for fitness, as a wave or bubble bath, or for underwater massage upon medical advice. Swimming without turning is possible even in small pools.

## Version

Like the BADU JET Vogue, but with stainless steel nozzles and controls and piezo buttons.

## Material short text

BJ Vogue Deluxe,FMS,1~,LED_W

## Technical data

### Hydraulic power

| | |
|---|---|
| Flow rate | 54 m³/h |

### Motor & drive

| | |
|---|---|
| Motor phases | 1~ |
| Degree of protection | IP X5 |
| Insulation class | F |

### Electrics

| | |
|---|---|
| Power input $P_1$ (max.) | 2.89 kW |
| Power output $P_2$ (max.) | 2.2 kW |
| Voltage (max.) | 1~ 230 V |
| Frequency | 50 Hz |

### General / Product features

| | |
|---|---|
| Product range | BADU Premium |

### Connections & piping

| | |
|---|---|
| Recommended suction line diameter | 63 mm |
| Recommended discharge line diameter | 63 mm |

### Nozzles & counter-current system

| | |
|---|---|
| Number of nozzles | 1 St |
| Nozzle swivels in all directions | 60 ° |
| Outlet pressure at the nozzle | 1 bar |
| Outlet velocity, centred 2 m in front of the nozzle | 1.1 m/s |
| Massage pressure max. | 0 bar |

### Operating conditions & water

| | |
|---|---|
| Ambient temperature (min.) | 40 ° C |
| Total salt concentration | 0.066 % |

## Dimensions & logistics

| | |
|---|---|
| Customs tariff number | 84798997 |