BADU JET TURBO PRO

BADU JET Turbo Pro Design 2 Standard-Montagesatz

Article number 2325120000
Product page https://www.speck-neos.medienreaktor-kunden.de/en/p/badu-jet-turbo-pro-design-2-standard-montagesatz-2325120000



Description

Innovation, performance, and elegant design combined. Welcome to the limit.

Areas of use

For wall installation in all pool designs up to 7 mm thick, except round pools. For performance-oriented professional workouts, relaxation, rehabilitation training, fitness, or recreational fun.

Version

A flush-mounted housing uses innovative propeller technology to draw water through the cover and return it to the pool in a powerful jet. The system is powered by an efficient, fanless, fully encapsulated permanent magnet motor. Power control and switching on and off are controlled via the integrated piezo buttons or a remote control.

Material short text

BJ Turbo Pro, Stand.-Montagesatz Design2

Technical data

Hydraulic power

Flow rate	150 – 350 m³/h

Electrics

Power input P_1 (max.)	2.75 kW
Power output P_2 (max.)	0 kW
Voltage (max.)	3~ 380-480 V

General / Product features

Product range	BADU Premium

Connections & piping

Recommended suction line diameter	0 mm
Recommended discharge line diameter	0 mm

Nozzles & counter-current system

Number of nozzles	1 St
Nozzle swivels in all directions	5 °
Outlet pressure at the nozzle	0 bar
Outlet velocity, centred 2 m in front of the nozzle	4.1 m/s
Massage pressure max.	0 bar

Operating conditions & water

Ambient temperature (min.)	0 ° C
Total salt concentration	0 %

Dimensions & logistics

Customs tariff number	84798997