
BADU GAMMA

BADU Gamma 23

Article number	2105230037
GTIN/EAN	4260673451424
Product page	https://www.speck-neos.medienreaktor-kunden.de/en/p/badu-gamma-23-2105230037



Description

The new bestseller after our BADU Prime Equipped with internal and external thread Efficient, modern, well thought out

Areas of use

Swimming pool water circulation in filter systems, can be installed max. 3 m above or below the water level

Version

Close-coupled pump with integrated fiber catcher. Bellows mechanical seal mounted on a plastic impeller hub. The motor or pump shaft does not come into contact with the circulating water. Electrically isolated. Fiber catcher capacity approx. 3 l Suction screen mesh size approx. 3.2 x 2.6 mm

Material short text

BADU Gamma 23, 3~, 1,00 kW, blau

Technical data

Hydraulic power

Flow rate	23 m³/h
Head (min.)	17.6 mWS

Motor & drive

Speed (max.)	2,840 min-1
Motor phases	3~
Degree of protection	IP 55
Insulation class	F

Electrics

Power input P_1 (max.)	1.2 kW

Power output P_2 (max.)	1 kW
Voltage (max.)	3~ Y/Δ 400/230 V
Frequency	50 Hz

Energy efficiency

Energy efficiency class	D

General / Product features

Certification	TÜV

Filtration

Lint catcher capacity	3 l

Connections & piping

Connection, inlet / suction side	63 mm / 2 Rp
Connection, discharge side	63 mm / 2 Rp
Recommended suction line diameter	63 mm
Recommended discharge line diameter	63 mm

Operating conditions & water

Ambient temperature (min.)	40 ° C
Total salt concentration	5 g/l

Dimensions & logistics

Product length	585 mm
Net weight	17.2 kg
Customs tariff number	84137051