
BADU GAMMA

BADU Gamma 29

Article number	2105290037
GTIN/EAN	4260673451431
Product page	https://www.speck-neos.medienreaktor-kunden.de/en/p/badu-gamma-29-2105290037



Description

The new bestseller after our BADU Prime Equipped with internal and external thread Efficient, modern, well thought out

Areas of use

Swimming pool water circulation in filter systems, can be installed max. 3 m above or below the water level

Version

Close-coupled pump with integrated fiber catcher. Bellows mechanical seal mounted on a plastic impeller hub. The motor or pump shaft does not come into contact with the circulating water. Electrically isolated. Fiber catcher capacity approx. 3 l Suction screen mesh size approx. 3.2 x 2.6 mm

Material short text

BADU Gamma 29, 3~, 1,30 kW, blau

Technical data

Hydraulic power

Flow rate	29 m³/h
Head (min.)	16.6 mWS

Motor & drive

Speed (max.)	2,840 min-1
Motor phases	3~
Degree of protection	IP 55
Insulation class	F

Electrics

Power input P_1 (max.)	1.54 kW

Power output P_2 (max.)	1.3 kW
Voltage (max.)	3~ Y/Δ 400/230 V
Frequency	50 Hz

Energy efficiency

Energy efficiency class	D

General / Product features

Certification	TÜV

Filtration

Lint catcher capacity	3 l

Connections & piping

Connection, inlet / suction side	75 mm / 2 Rp
Connection, discharge side	75 mm / 2 Rp
Recommended suction line diameter	75 mm
Recommended discharge line diameter	75 mm

Operating conditions & water

Ambient temperature (min.)	40 ° C
Total salt concentration	5 g/l

Dimensions & logistics

Product length	610 mm
Net weight	20 kg
Customs tariff number	84137051