BADU DELTA-MK

# BADU Delta-MK 8

| | |
|---|---|
| Article number | 2103080338 |
| GTIN/EAN | 4260673450915 |
| Product page | https://www.speck-neos.medienreaktor-kunden.de/en/p/badu-delta-mk-8-2103080338 |



## Description

Sealless pump for saltwater pools Extension of the quiet BADU Delta series

## Areas of use

Swimming pool water circulation in filter systems, can be installed max 1.5 m above or 3 m below the water level

## Version

Block pump with integrated fiber catcher. The motor or pump shaft does not come into contact with the circulating water. Electrically isolated. Fiber catcher capacity approx. 4 l Suction screen mesh size approx. 2.2 x 2.2 mm

## Material short text

BADU Delta-MK 8, 1~, 0,30 kW

## Technical data

### Hydraulic power

| | |
|---|---|
| Flow rate | 8 m³/h |
| Head (min.) | 10.6 mWS |

### Motor & drive

| | |
|---|---|
| Speed (max.) | 2,840 min-1 |
| Motor phases | 1~ |
| Degree of protection | IP 55 |
| Insulation class | F |

### Electrics

| | |
|---|---|
| Power input $P_1$ (max.) | 0.5 kW |
| Power output $P_2$ (max.) | 0.3 kW |

| | |
|---|---|
| Voltage (max.) | 1~ 230 V |
| Frequency | 50 Hz |

### General / Product features

| | |
|---|---|
| Certification | TÜV, Garantie 5 Jahre, Patent |

### Filtration

| | |
|---|---|
| Lint catcher capacity | 4 l |

### Connections & piping

| | |
|---|---|
| Connection, inlet / suction side | 50 mm |
| Connection, discharge side | 50 mm |
| Recommended suction line diameter | 50 mm |
| Recommended discharge line diameter | 50 mm |

### Operating conditions & water

| | |
|---|---|
| Ambient temperature (min.) | 40 ° C |
| Total salt concentration | 5 g/l |

## Dimensions & logistics

| | |
|---|---|
| Product length | 697 mm |
| Net weight | 0 kg |
| Customs tariff number | 84137051 |