TOP 150

TOP 150 VOX D

Article number 6422150127

Product page https://www.speck-neos.medienreaktor-kunden.de/en/p/top-150-vox-d-6422150127



Description

Optimal drainage through submersible pumps made of corrosion-resistant materials from Speck, offering a highly flexible application and use for more than just water.

Areas of use

Basement drainage Drainage of pump shafts Wastewater disposal Rainwater pumping Groundwater pumping

Version

Fully submersible submersible pump made of stainless steel. Motor with built-in thermal overload protection (for AC). Ready to connect with a 10 m cable and Schuko plug (for AC), with a free cable end (for three-phase). AC = AC 1~ 230 V, with floating switch D = Three-phase 3~ 400 V, without floating switch VOX = Open impeller Pump medium: Pure water, wastewater, and dirty water, without long-fiber components.

Material short text

TOP 150 VOX D, 1,10 kW

Technical data

Hydraulic power

Flow rate	36 m³/h
Head (min.)	11.5 mWS

Motor & drive

Speed (max.)	2,850 min-1
Motor phases	3~
Degree of protection	IP 68
Insulation class	F

Electrics

Power input P_1 (max.)	1.57 kW
Power output P_2 (max.)	1.1 kW
Voltage (max.)	3~ 400 V
Frequency	50 Hz
Cable length	10 m

Energy efficiency

Energy efficiency class	IE3

Connections & piping

Connection, discharge side	2 Rp

Dimensions & logistics

Product length	0 mm
Product width	0 mm
Product height	516 mm
Net weight	20.2 kg
Gross weight	0 kg
Customs tariff number	84137021