MTX 18

MTX 18-30

Article number 6441803067A

Product page https://www.speck-neos.medienreaktor-kunden.de/en/p/mtx-18-30-6441803067a



Description

Horizontal multistage pumps in close-coupled design with an extended motor shaft, designed for continuous operation. All wetted parts are made of stainless steel.

Areas of use

Water treatment Water supply Cooling systems Apparatus construction

Version

Close-coupled pump with surface-cooled motor, extended motor shaft for the impellers, shaft sealing by a mechanical seal, designed for continuous operation. Fluid: Clear, even moderately aggressive liquids that do not chemically or mechanically attack the pump materials. Special designs: Special voltages: Special elastomers: Special mechanical seals: Higher fluid temperatures:

Material short text

MTX 18-30, Dr., 2,20 kW

Technical data

Hydraulic power

Flow rate	27 m³/h
Head (min.)	36 mWS

Motor & drive

Speed (max.)	2,850 min-1
Motor phases	3~
Degree of protection	IP 55
Insulation class	F

Electrics

Power input P_1 (max.)	0 kW
Power output P_2 (max.)	2.2 kW
Voltage (max.)	3~ 230/400 V ± 10 %
Frequency	50 Hz

Dimensions & logistics

Customs tariff number	84137051