
EY MK

# EY 4281 MK

Product page https://www.speck-neos.medienreaktor-kunden.de/en/p/ey-4281-mk-p50982



## Description

Non-self-priming peripheral impeller pumps with magnetic coupling are characterized by high pressure at low flow rates and a compact design. Thanks to the magnetic coupling, they are leak-free and maintenance-free.

## Sales text

EY 4281 MK

## Areas of use

> Cooling circuits: Our pumps ensure reliable cooling in a variety of applications. > Temperature controls: They ensure precise and efficient temperature control.

## Technical data

### Hydraulic power

| | |
|---|---|
| Flow rate | 140 l/min |
| Head (min.) | 57 mWS |
| Operating pressure max. | 57 mWS |

### Motor & drive

| | |
|---|---|
| Speed (max.) | 2,800 min-1 |
| Degree of protection | IP 54 |

### Electrics

| | |
|---|---|
| Power output $P_2$ (max.) | 1 kW |
| Input voltage | 230 V |
| Frequency | 50 Hz |

### Connections & piping

| | |
|---|---|
| Connection, inlet / suction side | G 3/4" |

| | |
|---|---|
| Connection, discharge side | G 3/4" |

**Operating conditions & water**

| | |
|---|---|
| Ambient temperature (min.) | 40 ° C |

## Dimensions & logistics

| | |
|---|---|
| Customs tariff number | 84137045 |