
BADU PRIME

# BADU Prime 13

| | |
|---|---|
| Article number | 2190138037 |
| GTIN/EAN | 4260673451523 |
| Product page | https://www.speck-neos.medienreaktor-kunden.de/en/p/badu-prime-13-2190138037 |



## Description

Established and reliable premium circulation pump with 5-year quality guarantee

## Areas of use

Swimming pool water circulation in filter systems, can be installed max. 3 m above or below the water level

## Version

Close-coupled pump with integrated fiber catcher. Bellows mechanical seal mounted on a plastic impeller hub. The motor or pump shaft does not come into contact with the circulating water. Electrically isolated. Fiber catcher capacity approx. 3 l Suction screen mesh size approx. 3.2 x 2.6 mm

## Material short text

BADU Prime 13, 3~, 0,55kW, blau

## Technical data

### Hydraulic power

| | |
|---|---|
| Flow rate | 13 m³/h |
| Head (min.) | 14.7 mWS |
| Operating pressure max. | 0 bar |

### Motor & drive

| | |
|---|---|
| Speed (max.) | 2,840 min-1 |
| Motor phases | 3~ |
| Degree of protection | IP 55 |
| Insulation class | F |

### Electrics

| | |
|---|---|
| Power input $P_1$ (max.) | 0.69 kW |
| Power output $P_2$ (max.) | 0.55 kW |
| Voltage (max.) | 3~ Y/Δ 400/230 V |
| Frequency | 50 Hz |

### Energy efficiency

| | |
|---|---|
| Energy efficiency class | D |

### General / Product features

| | |
|---|---|
| Certification | TÜV, Garantie 5 Jahre |

### Filtration

| | |
|---|---|
| Lint catcher capacity | 3 l |

### Connections & piping

| | |
|---|---|
| Connection, inlet / suction side | 2 Rp |
| Connection, discharge side | 1 1/2 Rp |
| Recommended suction line diameter | 50 mm |
| Recommended discharge line diameter | 63 mm |

### Operating conditions & water

| | |
|---|---|
| Ambient temperature (min.) | 40 ° C |
| Total salt concentration | 5 g/l |

## Dimensions & logistics

| | |
|---|---|
| Product length | 507 mm |
| Net weight | 11.1 kg |
| Customs tariff number | 84137051 |