BC 90/40

BC 90/40

Article number 2190404337

Product page https://www.speck-neos.medienreaktor-kunden.de/en/p/bc-90-40-2190404337



Description

For reliable pumping of aggressive media

Areas of use

Pumping neutral and many non-neutral liquids, such as acids and bases, and aqueous solutions without abrasive components, e.g., in: - Surface technology - Environmental technology - Laboratory technology - Plastics industry - Rubber industry - Process engineering - Water treatment

Version

BC series plastic centrifugal pumps with mechanical seals are suitable for chemically neutral and many chemically non-neutral liquids. Many aqueous acids and bases can be pumped. The pumps are self-priming and feature a suction strainer. Reliable operation even with varying suction heads is ensured. Seals are available in Viton or EPDM. They are driven by standard three-phase or single-phase motors.

Material short text

BC 90/40 Viton. 3~. 3.00 kW.verst. Ausf.

Technical data

Motor & drive

Speed (max.)	2,865 min-1
Motor frame size	90
Motor protection	Kaltleiterfühler PTC
Degree of protection	IP 55
Insulation class	F

Electrics

Power input P_1 (max.)	3.44 kW
Power output P_2 (max.)	3 kW
Voltage (max.)	3~ 400/230 V
Rated current (230V)	10.9 A
Frequency	50 Hz

Energy efficiency

Energy efficiency class	IE3

Filtration

Lint catcher capacity	6 l
Strainer basket version	nein
Strainer basket mesh size	ca. 3.0 x 2.8 mm

Connections & piping

Connection, inlet / suction side	90
Connection, discharge side	90
Recommended suction line diameter	110 mm
Recommended discharge line diameter	110 mm

Operating conditions & water

Ambient temperature (min.)	40 ° C

Hydraulic power

Head (min.)	18.2 mWS

Dimensions & logistics

Product width	270 mm
Product height	434 mm
Net weight	34.5 kg
Customs tariff number	84137051