
AY MK

TOE AY 2251 PM

Product page https://www.speck-neos.medienreaktor-kunden.de/en/p/toe-ay-2251-pm-p52153



Description

Non-self-priming peripheral impeller pumps with magnetic coupling are characterized by high pressure at low flow rates and a compact design. Thanks to the magnetic coupling, they are leak-free and maintenance-free.

Sales text

TOE AY 2251 PM

Areas of use

> Cooling circuits: Our pumps ensure reliable cooling in a variety of applications. > Temperature controls: They ensure precise and efficient temperature control.

Technical data

Hydraulic power

Flow rate	48 l/min
Head (min.)	90 mWS
Operating pressure max.	90 mWS

Motor & drive

Speed (max.)	1,000 – 4,000 min-1
Motor phases	3~ (FU erforderlich)
Degree of protection	IP 54

Electrics

Power output P_2 (max.)	1.1 kW
Input voltage	400 V
Frequency	50 Hz

Energy efficiency

Energy efficiency class	IE3

Connections & piping

Connection, inlet / suction side	G 1/2" / SAE 1/2"
Connection, discharge side	G 1/2" / SAE 1/2"

Operating conditions & water

Ambient temperature (min.)	40 ° C

Dimensions & logistics

Customs tariff number	84137035