BADU 21-80

BADU 21-80/31R G

Article number	2380310137
GTIN/EAN	4260673452797
Product page	https://www.speck-neos.medienreaktor-kunden.de/en/p/badu-21-80-31r-g-2380310137



Description

Universal large circulation pump. Reliable and powerful. For whirlpools, counter-current systems, and swimming pool features.

Areas of use

Swimming pool and industrial filter systems, counter-current systems, air conditioning systems, swimming pool attractions, cleaning equipment and much more, up to 90 m³/h flow rate.

Version

Close-coupled pump with bellows mechanical seal, mounted on a plastic impeller hub. The motor or pump shaft does not come into contact with the circulating water. Electrically isolated. Discharge ports can be rotated 90° each and an additional 29° clockwise, viewed from the suction side. BADU 21-80/... SG conditionally self-priming up to 0.5 m upon request

Material short text

BADU 21-80/31R G, 3~, 1,60 kW, R 2 3/4

Technical data

Hydraulic power

Flow rate	48 m³/h
Head (min.)	0 – 9.5 mWS
Operating pressure max.	0 bar

Motor & drive

Speed (max.)	2,850 min-1
Motor phases	3~
Degree of protection	IP 55
Insulation class	F

Electrics

Power input P_1 (max.)	1.85 kW
Power output P_2 (max.)	1.6 kW
Voltage (max.)	3~ Y/Δ 400/230 V
Frequency	50 Hz

Filtration

Lint catcher capacity	0 l
Strainer basket version	-1

Connections & piping

Connection, inlet / suction side	2 3/4 G
Connection, discharge side	2 3/4 G
Recommended suction line diameter	110 mm
Recommended discharge line diameter	110 mm

Operating conditions & water

Ambient temperature (min.)	40 ° C
Total salt concentration	0 g/l

Dimensions & logistics

Product length	397 mm
Product width	0 mm
Product height	0 mm
Net weight	21 kg
Customs tariff number	84137051