BADU 21-81

BADU 21-81/33 G

Article number	2381330337
GTIN/EAN	4260673452902
Product page	https://www.speck-neos.medienreaktor-kunden.de/en/p/badu-21-81-33-g-2381330337



Description

Anschlussvariante der universellen Umwälzpumpe BADU 21-80. Für Whirlpools, Gegenstromanlagen und Schwimmbad-Attraktionen.

Areas of use

Freshwater, saltwater

Version

ringdichtung, auf Kunststoff□Laufradnabe montiert. Motor- bzw. Pumpenwelle kommt mit dem im Kreislauf befindlichen Wasser nicht in Berührung. Elektrische Trennung. Druckstutzen um je 90° und zusätzlich um 29° im Uhrzeigersinn, von der Saugseite gesehen, drehbar.

Material short text

BADU 21-81/33 G, 3~, 3,00 kW

Technical data

Hydraulic power

Flow rate	60 m³/h
Head (min.)	13.5 mWS
Operating pressure max.	0 bar

Motor & drive

Speed (max.)	2,850 min-1
Motor phases	3~
Degree of protection	IP 55
Insulation class	F

Electrics

Power input P_1 (max.)	3.44 kW
Power output P_2 (max.)	3 kW
Voltage (max.)	3~ Y/Δ 400/230 V
Frequency	50 Hz

Filtration

Lint catcher capacity	0 l

Connections & piping

Connection, inlet / suction side	90 mm
Connection, discharge side	90 mm
Recommended suction line diameter	110 mm
Recommended discharge line diameter	140 mm

Operating conditions & water

Ambient temperature (min.)	40 ° C
Total salt concentration	5 g/l

Dimensions & logistics

Product length	547 mm
Product width	0 mm
Product height	0 mm
Net weight	30 kg
Customs tariff number	84137051