BADU EASYFIT

BADU EasyFit 36

Article number	2076380038
GTIN/EAN	4260673451691
Product page	https://www.speck-neos.medienreaktor-kunden.de/en/p/badu-easyfit-36-2076380038



Description

Flexibility champion with 6 different connection sets. For use in virtually any filter system, regardless of manufacturer.

Areas of use

Swimming pool water circulation in filter systems, which can be installed a maximum of 3 m above or below the water level.

Version

Close-coupled pump with integrated fiber catcher. Bellows mechanical seal mounted on a plastic impeller hub. The motor or pump shaft does not come into contact with the circulating water. Electrically isolated. Fiber catcher capacity approx. 3 l Suction screen mesh size approx. 3.2 x 2.6 mm

Material short text

BADU EasyFit 36, 1~, 1,80 kW

Technical data

Hydraulic power

Flow rate	36 m³/h
Head (min.)	19 mWS

Motor & drive

Speed (max.)	2,840 min-1
Motor phases	1~
Degree of protection	IP 55
Insulation class	F

Electrics

Power input P_1 (max.)	2.2 kW

Power output P_2 (max.)	1.8 kW
Voltage (max.)	1~ 230 V
Frequency	50 Hz

Energy efficiency

Energy efficiency class	D

General / Product features

Certification	TÜV, Patent

Filtration

Lint catcher capacity	3 l

Connections & piping

Connection, inlet / suction side	75 mm
Connection, discharge side	75 mm
Recommended suction line diameter	75 mm
Recommended discharge line diameter	75 mm

Operating conditions & water

Ambient temperature (min.)	40 ° C
Total salt concentration	5 g/l

Dimensions & logistics

Product length	599 mm
Net weight	21.5 kg
Customs tariff number	84137051