BADU EASYFIT

BADU EasyFit 29

Article number	2076320037
GTIN/EAN	4260673451769
Product page	https://www.speck-neos.medienreaktor-kunden.de/en/p/badu-easyfit-29-2076320037



Description

Flexibility champion with 6 different connection sets For manufacturer-independent use in virtually any filter system

Areas of use

Swimming pool water circulation in filter systems, can be installed max. 3 m above or below the water level

Version

Close-coupled pump with integrated fiber catcher. Bellows mechanical seal mounted on a plastic impeller hub. The motor or pump shaft does not come into contact with the circulating water. Electrically isolated. Fiber catcher capacity approx. 3 l Suction screen mesh size approx. 3.2 x 2.6 mm

Material short text

BADU EasyFit 29, 3~, 1,30 kW

Technical data

Hydraulic power

Flow rate	29 m³/h
Head (min.)	17 mWS

Motor & drive

Speed (max.)	2,840 min-1
Motor phases	3~
Degree of protection	IP 55
Insulation class	F

Electrics

Power input P_1 (max.)	1.65 kW

Power output P_2 (max.)	1.3 kW
Voltage (max.)	3~ Y/Δ 400/230 V
Frequency	50 Hz

Energy efficiency

Energy efficiency class	C

General / Product features

Certification	TÜV, Patent

Filtration

Lint catcher capacity	3 l

Connections & piping

Connection, inlet / suction side	63 mm
Connection, discharge side	63 mm
Recommended suction line diameter	63 mm
Recommended discharge line diameter	75 mm

Operating conditions & water

Ambient temperature (min.)	40 ° C
Total salt concentration	5 g/l

Dimensions & logistics

Product length	597 mm
Net weight	16.7 kg
Customs tariff number	84137051