BADU EASYFIT ECO VS

BADU EasyFit Eco VS

Article number	2076261138
GTIN/EAN	4260673452018
Product page	https://www.speck-neos.medienreaktor-kunden.de/en/p/badu-easyfit-eco-vs-2076261138



Description

Pump universalist with good genes Wide range of applications with high flexibility

Version

Close-coupled pump with integrated fiber catcher. Bellows mechanical seal mounted on a plastic impeller hub. The motor or pump shaft does not come into contact with the circulating water. Electrically isolated. Fiber catcher capacity approx. 3 l Suction screen mesh size approx. 3.2 x 2.6 mm

Material short text

BADU EasyFit Eco VS, 1~, 1,10 kW

Technical data

Hydraulic power

Flow rate	25 m³/h
Head (min.)	22.3 mWS

Motor & drive

Speed (max.)	600 – 3,000 min-1
Motor phases	1~
Degree of protection	IP 55
Insulation class	F

Electrics

Power input P_1 (max.)	0.03 – 1.4 kW
Power output P_2 (max.)	0.01 – 1.1 kW
Voltage (max.)	1~ 230 V
Frequency	50 Hz

General / Product features

Product range	BADU Premium, BADU Green
Certification	TÜV, Patent, Green

Filtration

Lint catcher capacity	3 l

Connections & piping

Connection, inlet / suction side	63 mm
Connection, discharge side	63 mm
Recommended suction line diameter	63 mm
Recommended discharge line diameter	63 mm

Acoustics

Sound pressure level (min.)	35.4 – 67.3 dB[A]

Operating conditions & water

Ambient temperature (min.)	40 ° C
Total salt concentration	5 g/l

Dimensions & logistics

Product length	620 mm
Net weight	12.5 kg
Customs tariff number	84137051