BADU SUPER PRO RP 2

BADU SuperPro 40

Article number 2192485038

Product page https://www.speck-neos.medienreaktor-kunden.de/en/p/badu-superpro-40-2192485038



Description

Saltwater-optimized circulation pumps with drive-pump separation. For longer service life in corrosive environments.

Areas of use

Swimming pool water circulation in filter systems, which can be installed a maximum of 3 m above or below the water level.

Version

Close-coupled pump with integrated fiber catcher. Bellows mechanical seal mounted on a plastic impeller hub. The motor or pump shaft does not come into contact with the circulating water. Electrically isolated. Fiber catcher capacity approx. 3 l Suction screen mesh size approx. 3.2 x 2.6 mm

Material short text

BADU SuperPro 40, Rp 2, 1~, 2,20kW

Technical data

Hydraulic power

Flow rate	40 m³/h
Head (min.)	19.6 mWS
Operating pressure max.	0 bar

Motor & drive

Speed (max.)	2,840 min-1
Motor phases	1~
Degree of protection	IP 55
Insulation class	F

Electrics

Power input P_1 (max.)	2.92 kW
Power output P_2 (max.)	2.2 kW
Voltage (max.)	1~ 230 V
Frequency	50 Hz
Cable length	3 m

General / Product features

Product range	BADU Allround
Certification	TÜV

Filtration

Lint catcher capacity	3 l

Connections & piping

Connection, inlet / suction side	63 mm / 2 Rp
Connection, discharge side	63 mm / 2 Rp
Recommended suction line diameter	75 mm
Recommended discharge line diameter	75 mm

Operating conditions & water

Ambient temperature (min.)	40 ° C
Total salt concentration	5 g/l

Dimensions & logistics

Product length	592 mm
Product width	224 mm
Product height	295 mm
Net weight	22.2 kg
Customs tariff number	84137051