BADU TOP II

BADU Top II/14

Article number	2190148138
GTIN/EAN	4260673450748
Product page	https://www.speck-neos.medienreaktor-kunden.de/en/p/badu-top-ii-14-2190148138



Description

Proven long-lasting performance with high flexibility and performance. For medium-sized pools, above-ground pools, or smaller swimming ponds.

Areas of use

Swimming pool water circulation in filter systems, which can be installed a maximum of 3 m above or below the water level.

Version

Close-coupled pump with integrated fiber catcher. Bellows mechanical seal mounted on a plastic impeller hub. The motor or pump shaft does not come into contact with the circulating water. Electrically isolated. Fiber catcher capacity approx. 3 l Suction screen mesh size approx. 3.2 x 2.6 mm

Material short text

BADU Top II/14, 1~, 0,65kW, mit 3m

Technical data

Hydraulic power

Flow rate	14 m³/h
Head (min.)	16.5 mWS

Motor & drive

Speed (max.)	2,840 min-1
Motor phases	1~
Degree of protection	IP 55
Insulation class	F

Electrics

Power input P_1 (max.)	0.97 kW
Power output P_2 (max.)	0.65 kW
Voltage (max.)	1~ 230 V
Frequency	50 Hz
Cable length	3 m

General / Product features

Product range	BADU Allround
Certification	TÜV

Filtration

Lint catcher capacity	3 l

Connections & piping

Connection, inlet / suction side	2 Rp
Connection, discharge side	1 1/2 Rp
Recommended suction line diameter	63 mm
Recommended discharge line diameter	50 mm

Operating conditions & water

Ambient temperature (min.)	40 ° C
Total salt concentration	5 g/l

Dimensions & logistics

Product length	485 mm
Product width	196 mm
Product height	300 mm
Net weight	11.6 kg
Customs tariff number	84137051