BC 40/6

BC 40/6

Article number 2040063438

Product page https://www.speck-neos.medienreaktor-kunden.de/en/p/bc-40-6-2040063438



Description

For reliable pumping of aggressive media

Areas of use

Pumping neutral and many non-neutral liquids, such as acids and bases, and aqueous solutions without abrasive components, e.g., in: - Surface technology - Environmental technology - Laboratory technology - Plastics industry - Rubber industry - Process engineering - Water treatment

Version

BC series plastic centrifugal pumps with mechanical seals are suitable for chemically neutral and many chemically non-neutral liquids. Many aqueous acids and bases can be pumped. The pumps are self-priming and feature a suction strainer. Reliable operation even with varying suction heads is ensured. Seals are available in Viton or EPDM. They are driven by standard three-phase or single-phase motors.

Material short text

BC 40/6 A-Viton. 1~. 0.45kW.verst. Ausf.

Technical data

Motor & drive

Speed (max.)	2,820 min-1
Motor frame size	80
Motor protection	WSK 150 °C
Degree of protection	IP 55
Insulation class	F

Electrics

Power input P_1 (max.)	0.61 kW
Power output P_2 (max.)	0.45 kW

Voltage (max.)	1~ 230 V
Rated current (230V)	2.6 A
Frequency	50 Hz

Operating conditions & water

Ambient temperature (min.)	40 ° C

Hydraulic power

Head (min.)	10 mWS

Energy efficiency

Energy efficiency class	IE2

Filtration

Lint catcher capacity	0.5 l
Strainer basket version	Ja
Strainer basket mesh size	ca. 2.8 mm x 2. 8 mm

Connections & piping

Connection, inlet / suction side	2 1/4"
Connection, discharge side	2 1/4"
Recommended suction line diameter	50 mm
Recommended discharge line diameter	50 mm

Dimensions & logistics

Product width	184 mm
Product height	268 mm
Customs tariff number	84137051