BC 40/9

BC 40/9

Article number 2040094337

Product page https://www.speck-neos.medienreaktor-kunden.de/en/p/bc-40-9-2040094337



Description

For reliable pumping of aggressive media

Areas of use

Pumping neutral and many non-neutral liquids, such as acids and bases, and aqueous solutions without abrasive components, e.g., in: - Surface technology - Environmental technology - Laboratory technology - Plastics industry - Rubber industry - Process engineering - Water treatment

Version

BC series plastic centrifugal pumps with mechanical seals are suitable for chemically neutral and many chemically non-neutral liquids. Many aqueous acids and bases can be pumped. The pumps are self-priming and feature a suction strainer. Reliable operation even with varying suction heads is ensured. Seals are available in Viton or EPDM. They are driven by standard three-phase or single-phase motors.

Material short text

BC 40/9 A-Viton. 3~. 0.55kW.verst. Ausf.

Technical data

Motor & drive

Speed (max.)	2,850 min-1
Motor frame size	80
Motor protection	nein
Degree of protection	IP 55
Insulation class	F

Electrics

Power input P_1 (max.)	0.69 kW
Power output P_2 (max.)	0.55 kW

Voltage (max.)	3~ 400/230 V
Rated current (230V)	2.3 A
Rated current (400V)	1.3 A
Frequency	50 Hz

Operating conditions & water

Ambient temperature (min.)	40 ° C

Hydraulic power

Head (min.)	11.6 mWS

Energy efficiency

Energy efficiency class	IE3

Filtration

Lint catcher capacity	0.5 l
Strainer basket version	Ja
Strainer basket mesh size	ca. 2.8 mm x 2. 8 mm

Connections & piping

Connection, inlet / suction side	G 2 1/4 "
Connection, discharge side	G 2 1/4 "
Recommended suction line diameter	50 mm
Recommended discharge line diameter	50 mm

Dimensions & logistics

Product width	184 mm
Product height	268 mm
Net weight	9.8 kg
Customs tariff number	84137051