NORMBLOCK BINERO 40

# Normblock Binero 40-200

Product page https://www.speck-neos.medienreaktor-kunden.de/en/p/normblock-binero-40-200-p53049




## Description

Characteristic curves, as well as dimensional drawings and the various material combinations can be found in detail in our design program at speck-select.com

## Areas of use

Swimming pool water circulation for filtration and filter flushing, as well as the operation of swimming pool attractions in public swimming pools. > Outdoor and indoor pools > Thermal, medicinal, and spa baths > Pools with elevated brine concentrations > Water treatment, e.g., filter system construction > Leisure facilities > Attractions, e.g., water slides > Shipbuilding > Industry, e.g., cooling water systems > Water supply, e.g., irrigation

## Version

The Normblock Binero is a single-stage, non-self-priming volute casing pump with power ratings and main dimensions according to NF E 44-112 and DIN EN 733 (replacement for DIN 24255).

## Technical data

### Hydraulic power

| | |
|---|---|
| Head (min.) | 38 mWS |
| Operating pressure max. | 10 bar |

### Motor & drive

| | |
|---|---|
| Speed (max.) | 50 min-1 |
| Degree of protection | IP 55 |
| Insulation class | F |

### Electrics

| | |
|---|---|
| Frequency | 50 Hz |

### Operating conditions & water

| | |
|---|---|
| Ambient temperature (min.) | 40 ° C |