
P11

P11-10-150D

Product page https://www.speck-neos.medienreaktor-kunden.de/en/p/p11-10-150d-p53185



Description

High-pressure plunger pumps of the P 11 D series are oscillating positive displacement pumps and therefore offer high efficiency due to the direct, low-loss movement of the fluid. They reliably generate high fluid pressure with water at temperatures up to 105 °C. Compared to rotating positive displacement pumps, they enable more precise pumping at high pressures and low flow rates, making them particularly efficient for demanding applications.

Sales text

P11/10-150D

Areas of use

Various industrial processes: They are ideal for various industrial processes requiring precise pumping at high pressures. Steam boiler systems: They are used in steam boiler systems to generate reliable, high liquid pressure.

Technical data

Hydraulic power

Flow rate	6.5 l/min
Head (min.)	611.83 mWS
Operating pressure max.	60 bar

Motor & drive

Speed (max.)	750 – 900 min-1

Electrics

Power input max.	0.8 kW
Frequency	50 Hz

Connections & piping

Connection, inlet / suction side	2x G1/2"

Connection, discharge side	2x G3/8"

Operating conditions & water

Ambient temperature (min.)	40 ° C
Temperature min.	90 ° C

Dimensions & logistics

Customs tariff number	84135080