2 VGX 20

# 2 VGX 20/50

Article number 6412409137A

Product page https://www.speck-neos.medienreaktor-kunden.de/en/p/2-vgx-20-50-6412409137a



## Description

Horizontal, single- or two-stage pumps in close-coupled design. They are characterized by a compact design and a long service life. All wetted parts are made of stainless steel.

## Areas of use

Water treatment Water supply Cooling systems Apparatus construction

## Version

Close-coupled pump with surface-cooled motor, extended motor shaft for the impellers, shaft sealing by a mechanical seal, designed for continuous operation. Fluid: Clear, even moderately aggressive liquids that do not chemically or mechanically attack the pump materials. Special designs: Special voltages: Special elastomers: Special mechanical seals: Higher fluid temperatures:

## Material short text

2 VGX 20/50, 3~, 3,70 kW

## Technical data

### Hydraulic power

| | |
|---|---|
| Flow rate | 12.5 m³/h |
| Head (min.) | 75 mWS |

### Motor & drive

| | |
|---|---|
| Speed (max.) | 2,850 min-1 |
| Motor phases | 3~ |
| Degree of protection | IP 55 |
| Insulation class | F |

### Electrics

| | |
|---|---|
| Power input $P_1$ (max.) | 0 kW |
| Power output $P_2$ (max.) | 3.7 kW |
| Voltage (max.) | 3~ 230/400 V ± 10 % |
| Frequency | 50 Hz |

## Dimensions & logistics

| | |
|---|---|
| Net weight | 35.6 kg |
| Customs tariff number | 84137075 |