BADU DELTA DR.

BADU Delta 22

Article number	2103220038
GTIN/EAN	4260673450830
Product page	https://www.speck-neos.medienreaktor-kunden.de/en/p/badu-delta-22-2103220038



Description

New high-class standard for demanding projects High-quality filter circulation pumps for professionals

Areas of use

Swimming pool water circulation in filter systems, can be installed max. 3 m above or below the water level

Version

Close-coupled pump with integrated fiber catcher. Bellows mechanical seal mounted on a plastic impeller hub. The motor or pump shaft does not come into contact with the circulating water. Electrically isolated. Fiber catcher capacity approx. 4 l Suction screen mesh size approx. 2.2 x 2.2 mm

Material short text

BADU Delta 22, 1~, 0,75 kW

Technical data

Hydraulic power

Flow rate	22 m³/h
Head (min.)	15 mWS

Motor & drive

Speed (max.)	2,840 min-1
Motor phases	1~
Degree of protection	IP 55
Insulation class	F

Electrics

Power input P_1 (max.)	1.03 kW

Power output P_2 (max.)	0.75 kW
Voltage (max.)	1~ 230 V
Frequency	50 Hz

General / Product features

Certification	TÜV, Garantie 5 Jahre, Patent

Filtration

Lint catcher capacity	4 l

Connections & piping

Connection, inlet / suction side	63 mm
Connection, discharge side	63 mm
Recommended suction line diameter	63 mm
Recommended discharge line diameter	63 mm

Operating conditions & water

Ambient temperature (min.)	40 ° C
Total salt concentration	5 g/l

Dimensions & logistics

Product length	572 mm
Net weight	15.6 kg
Customs tariff number	84137051