FEUERCELL SUPS

SUPS 18-7 (3 ~400V)

Article number 5161807001

Product page https://www.speck-neos.medienreaktor-kunden.de/en/p/sups-18-7-3-400v-5161807001



Description

Die Unterwasserpumpen zeichnen sich durch eine hohe Wirtschaftlichkeit, lange Lebensdauer und einen gekapselten Unterwassermotor aus. Alle medium berührten Teile sind aus Edelstahl.

Areas of use

> Löschwasserversorgung

> Beregnung

> Wasserversorgung

Material short text

SUPS 18-7. Dr.. 4.0 kW

Technical data

Hydraulic power

Flow rate	22 m³/h
Head (min.)	78 mWS
Operating pressure max.	25 bar

Motor & drive

Speed (max.)	2,800 min-1
Degree of protection	IP 68
Insulation class	B

Electrics

Power output P_2 (max.)	4 kW
Voltage (max.)	3~ 400 V ± 10 %
Frequency	50 Hz

Energy efficiency

Energy efficiency class	IE3

Connections & piping

Connection, inlet / suction side	2 1/2 DN
Connection, discharge side	2 1/2 DN

Operating conditions & water

Ambient temperature (min.)	30 ° C
Temperature min.	30 ° C

Dimensions & logistics

Net weight	45 kg