BADU JET Vogue

Product page https://www.speck-neos.medienreaktor-kunden.de/en/p/badu-jet-vogue-p53569



Description

An attractive design system for discerning customers. Red Dot award-winning aesthetics with a stainless steel panel.

Areas of use

For wall installation in all pool designs, as an attraction, for fitness, as a wave or bubble bath, or for underwater massage upon medical advice. Swimming without turning is possible even in small pools.

Version

Like the BADU JET Vogue, but with stainless steel nozzles and controls and piezo buttons.

Technical data

Motor & drive

Speed (max.)	2,850 min-1
Degree of protection	IP X5
Insulation class	F

Electrics

Frequency	50 Hz

General / Product features

Product range	BADU Premium

Connections & piping

Recommended suction line diameter	63 mm
Recommended discharge line diameter	63 mm

Nozzles & counter-current system

Number of nozzles	1 St

Nozzle swivels in all directions	60 °

Operating conditions & water

Ambient temperature (min.)	40 ° C
Total salt concentration	0.066 %

Dimensions & logistics

Customs tariff number	84798997

Variants

Article number	Name	Flow rate	Motor phases	Power input P_1 (max.)	Power output P_2 (max.)	Voltage (max.)	Outlet pressure at the nozzle	Outlet velocity, centred 2 m in front of the nozzle	Massage pressure max.
2322220000	BADU JET Vogue mit Multicolor-LED Fertigmontagesatz	58 m³/h	3~	3.18 kW	2.6 kW	3 N~ 400/230 V	1.1 bar	1.2 m/s	1.6 bar
2322420000	BADU JET Vogue mit Multicolor-LED Fertigmontagesatz	54 m³/h	1~	2.89 kW	2.2 kW	1~ 230 V	1 bar	1.1 m/s	1.4 bar
2322200000	BADU JET Vogue mit weißer LED Fertigmontagesatz	58 m³/h	3~	3.18 kW	2.6 kW	3 N~ 400/230 V	1.1 bar	1.2 m/s	1.6 bar
2322400000	BADU JET Vogue mit weißer LED Fertigmontagesatz	54 m³/h	1~	2.89 kW	2.2 kW	1~ 230 V	1 bar	1.1 m/s	1.4 bar