BADU 21-40

Product page https://www.speck-neos.medienreaktor-kunden.de/en/p/badu-21-40-p53577

Technical data

Motor & drive

Speed (max.)	2,850 min-1
Degree of protection	IP 55
Insulation class	F

Electrics

Frequency	50 Hz

Connections & piping

Connection, inlet / suction side	2 G
Connection, discharge side	2 G

Operating conditions & water

Total salt concentration	5 g/l

Dimensions & logistics

Customs tariff number	84137051

Variants

Article number	Name	Flow rate	Head (min.)	Operating pressure max.	Motor phases	Power input P_1 (max.)	Power output P_2 (max.)	Voltage (max.)	Recommended suction line diameter	Recommended discharge line diameter	Lint catcher capacity	Ambient temperature (min.)
2340630137	BADU 21-40/63 G	17 m³/h	0 – 12.4 mWS	2.5 bar	3~	0.75 kW	0.55 kW	3~ 400/230 V	63 mm	63 mm	–	–
2340630138	BADU 21-40/63 G	16 m³/h	12.4 mWS	–	1~	0.85 kW	0.55 kW	1~ 230 V	63 mm	63 mm	0 l	40 ° C
2340630147	BADU 21-40/63 G-AK	17 m³/h	0 – 12.4 mWS	–	–	0.75 kW	0.55 kW	–	–	–	–	–
2340630338	BADU 21-40/63H G	10 m³/h	17.5 mWS	–	1~	0.85 kW	0.55 kW	1~ 230 V	63 mm	63 mm	0 l	40 ° C
2340636337	BADU 21-40/63H G	10 m³/h	0 – 17.5 mWS	2.5 bar	3~	0.75 kW	0.55 kW	3~ 400/230 V	63 mm	63 mm	–	–

Article number	Name	Flow rate	Head (min.)	Operating pressure max.	Motor phases	Power input P_1 (max.)	Power output P_2 (max.)	Voltage (max.)	Recommended suction line diameter	Recommended discharge line diameter	Lint catcher capacity	Ambient temperature (min.)
2340630447	BADU 21-40/63HG-AK	10 m³/h	0 – 17.5 mWS	–	–	0.75 kW	0.55 kW	–	–	–	–	–
2340640137	BADU 21-40/64G	18 m³/h	0 – 13 mWS	2.5 bar	3~	1.1 kW	0.75 kW	3~ 400/230 V	63 mm	63 mm	–	–
2340640138	BADU 21-40/64G	18 m³/h	13 mWS	–	1~	1.05 kW	0.75 kW	1~ 230 V	63 mm	63 mm	0 l	40 ° C
2340640147	BADU 21-40/64G-AK	18 m³/h	0 – 13 mWS	–	–	1.1 kW	0.75 kW	–	–	–	–	–
2340640337	BADU 21-40/64HG	14 m³/h	0 – 19 mWS	2.5 bar	3~	1.1 kW	0.75 kW	3~ 400/230 V	63 mm	63 mm	–	–
2340640338	BADU 21-40/64HG	14 m³/h	19 mWS	–	1~	1.05 kW	0.75 kW	1~ 230 V	63 mm	63 mm	0 l	40 ° C
2340640347	BADU 21-40/64HG-AK	14 m³/h	0 – 19 mWS	–	–	1.1 kW	0.75 kW	–	–	–	–	–
2340650138	BADU 21-40/65G	19 m³/h	0 – 14 mWS	2.5 bar	1~	1.4 kW	1 kW	1~ 230 V	63 mm	63 mm	0 l	40 ° C
2340650338	BADU 21-40/65HG	19 m³/h	0 – 21 mWS	2.5 bar	1~	1.4 kW	1 kW	1~ 230 V	63 mm	63 mm	0 l	40 ° C
2340660137	BADU 21-40/66G	20 m³/h	0 – 21 mWS	2.5 bar	3~	1.5 kW	1.1 kW	3~ 400/230 V	63 mm	63 mm	0 l	40 ° C
2340660047	BADU 21-40/66G-AK	20 m³/h	0 – 21 mWS	2.5 bar	3~	1.5 kW	1.1 kW	3~ 400/230 V	63 mm	63 mm	–	–
2340660337	BADU 21-40/66HG	19 m³/h	0 – 21 mWS	2.5 bar	3~	1.5 kW	1.1 kW	3~ 400/230 V	63 mm	63 mm	0 l	40 ° C
2340660647	BADU 21-40/66HG-AK	19 m³/h	0 – 21 mWS	2.5 bar	3~	1.5 kW	1.1 kW	3~ 400/230 V	63 mm	63 mm	–	–
2340680137	BADU 21-40/68G-AK	20 m³/h	0 – 18 mWS	2.5 bar	3~	1.9 kW	1.5 kW	3~ 400/230 V	75 mm	75 mm	0 l	40 ° C

Article number	Name	Flow rate	Head (min.)	Operating pressure max.	Motor phases	Power input P_1 (max.)	Power output P_2 (max.)	Voltage (max.)	Recommended suction line diameter	Recommended discharge line diameter	Lint catcher capacity	Ambient temperature (min.)
2340680138	BADU 21-40/68 G	20 m³/h	18 mWS	–	1~	2 kW	1.5 kW	1~ 230 V	75 mm	75 mm	0 l	40 ° C
2340680137	BADU 21-40/68 G-AK	20 m³/h	0 – 21.7 mWS	2.5 bar	3~	1.9 kW	1.5 kW	–	75 mm	75 mm	–	–
2340680337	BADU 21-40/68HG	24 m³/h	0 – 22 mWS	2.5 bar	3~	1.9 kW	1.5 kW	3~ 400/230 V	75 mm	75 mm	0 l	40 ° C
2340680338	BADU 21-40/68HG	24 m³/h	22 mWS	–	1~	2 kW	1.5 kW	1~ 230 V	75 mm	75 mm	0 l	40 ° C