BADU Delta Dr.

Product page https://www.speck-neos.medienreaktor-kunden.de/en/p/badu-delta-dr-p53601



Description

New high-class standard for demanding projects High-quality filter circulation pumps for professionals

Areas of use

Swimming pool water circulation in filter systems, can be installed max. 3 m above or below the water level

Version

Close-coupled pump with integrated fiber catcher. Bellows mechanical seal mounted on a plastic impeller hub. The motor or pump shaft does not come into contact with the circulating water. Electrically isolated. Fiber catcher capacity approx. 4 l Suction screen mesh size approx. 2.2 x 2.2 mm

Technical data

Motor & drive

Speed (max.)	2,840 min-1
Degree of protection	IP 55
Insulation class	F

Electrics

Frequency	50 Hz

General / Product features

Certification	TÜV, Garantie 5 Jahre, Patent

Filtration

Lint catcher capacity	4 l

Operating conditions & water

Ambient temperature (min.)	40 ° C

Total salt concentration	5 g/l

Dimensions & logistics

Customs tariff number	84137051

Variants

Article number	Name	Flow rate	Head (min.)	Motor phases	Power input P_1 (max.)	Power output P_2 (max.)	Voltage (max.)	Connection, inlet / suction side	Connection, discharge side	Recommended suction line diameter	Recommended discharge line diameter
2103120037	BADU Delta 13	13 m³/h	13.5 mWS	3~	0.63 kW	0.45 kW	3~ Y/Δ 400/230 V	63 mm	63 mm	63 mm	63 mm
2103120038	BADU Delta 13	13 m³/h	13.5 mWS	1~	0.61 kW	0.45 kW	1~ 230 V	63 mm	63 mm	63 mm	63 mm
2103170037	BADU Delta 17	17 m³/h	14.3 mWS	3~	0.69 kW	0.55 kW	3~ Y/Δ 400/230 V	63 mm	63 mm	63 mm	63 mm
2103170038	BADU Delta 17	17 m³/h	14.3 mWS	1~	0.72 kW	0.55 kW	1~ 230 V	63 mm	63 mm	63 mm	63 mm
2103220037	BADU Delta 22	22 m³/h	15 mWS	3~	0.9 kW	0.75 kW	3~ Y/Δ 400/230 V	63 mm	63 mm	63 mm	63 mm
2103220038	BADU Delta 22	22 m³/h	15 mWS	1~	1.03 kW	0.75 kW	1~ 230 V	63 mm	63 mm	63 mm	63 mm
2103280037	BADU Delta 28	28 m³/h	16 mWS	3~	1.2 kW	1 kW	3~ Y/Δ 400/230 V	63 mm	63 mm	75 mm	75 mm
2103280038	BADU Delta 28	28 m³/h	16 mWS	1~	1.29 kW	1 kW	1~ 230 V	63 mm	63 mm	75 mm	75 mm
2103070037	BADU Delta 9	9 m³/h	12.7 mWS	3~	0.41 kW	0.3 kW	3~ Y/Δ 400/230 V	50 mm	50 mm	50 mm	50 mm
2103070038	BADU Delta 9	9 m³/h	12.7 mWS	1~	0.46 kW	0.3 kW	1~ 230 V	50 mm	50 mm	50 mm	50 mm