BADU Delta-MK

Product page https://www.speck-neos.medienreaktor-kunden.de/en/p/badu-delta-mk-p53605



Description

Sealless pump for saltwater pools Extension of the quiet BADU Delta series

Areas of use

Swimming pool water circulation in filter systems, can be installed max 1.5 m above or 3 m below the water level

Version

Block pump with integrated fiber catcher. The motor or pump shaft does not come into contact with the circulating water. Electrically isolated. Fiber catcher capacity approx. 4 l Suction screen mesh size approx. 2.2 x 2.2 mm

Technical data

Motor & drive

Speed (max.)	2,840 min-1
Degree of protection	IP 55
Insulation class	F

Electrics

Frequency	50 Hz

General / Product features

Certification	TÜV, Garantie 5 Jahre, Patent

Filtration

Lint catcher capacity	4 l

Operating conditions & water

Ambient temperature (min.)	40 ° C
Total salt concentration	5 g/l

Dimensions & logistics

Customs tariff number	84137051

Variants

Article number	Name	Flow rate	Head (min.)	Motor phases	Power input P_1 (max.)	Power output P_2 (max.)	Voltage (max.)	Connection, inlet / suction side	Connection, discharge side	Recommended suction line diameter	Recommended discharge line diameter
2103120337	BADU Delta-MK 12	12 m³/h	11.5 mWS	3~	0.63 kW	0.45 kW	3~ Y/Δ 400/230 V	63 mm	63 mm	63 mm	63 mm
2103120338	BADU Delta-MK 12	12 m³/h	11.5 mWS	1~	0.65 kW	0.45 kW	1~ 230 V	63 mm	63 mm	63 mm	63 mm
2103160337	BADU Delta-MK 16	16 m³/h	12.8 mWS	3~	0.97 kW	0.65 kW	3~ Y/Δ 400/230 V	63 mm	63 mm	63 mm	63 mm
2103160338	BADU Delta-MK 16	16 m³/h	12.8 mWS	1~	0.97 kW	0.65 kW	1~ 230 V	63 mm	63 mm	63 mm	63 mm
2103200337	BADU Delta-MK 20	20 m³/h	14.6 mWS	3~	0.93 kW	0.75 kW	3~ Y/Δ 400/230 V	63 mm	63 mm	63 mm	63 mm
2103200338	BADU Delta-MK 20	20 m³/h	14.6 mWS	1~	1.1 kW	0.75 kW	1~ 230 V	63 mm	63 mm	63 mm	63 mm
2103270337	BADU Delta-MK 27	27 m³/h	15.1 mWS	3~	1.26 kW	1 kW	3~ Y/Δ 400/230 V	63 mm	63 mm	75 mm	75 mm
2103270338	BADU Delta-MK 27	27 m³/h	15.1 mWS	1~	1.4 kW	1 kW	1~ 230 V	63 mm	63 mm	75 mm	75 mm
2103080337	BADU Delta-MK 8	8 m³/h	10.6 mWS	3~	0.5 kW	0.3 kW	3~ Y/Δ 400/230 V	50 mm	50 mm	50 mm	50 mm
2103080338	BADU Delta-MK 8	8 m³/h	10.6 mWS	1~	0.5 kW	0.3 kW	1~ 230 V	50 mm	50 mm	50 mm	50 mm