BADU Eco Future We.

Product page https://www.speck-neos.medienreaktor-kunden.de/en/p/badu-eco-future-we-p53612



Description

A world first made from bio-based plastic. Innovation combined with design and maximum sustainability.

Areas of use

Schwimmbadwasser-Umwälzung in Filteranlagen, aufstellbar jeweils max. 3m oberhalb oder unterhalb des Wasserniveaus

Version

Blockpumpe mit integriertem Fasernfänger.
Bald-Gleitringdichtung auf Kunststoff-Laufradnabe montiert.
Motor- bzw. Pumpenwelle kommt mit dem im kreislauf befindlichen Wasser nicht in Berührung. Elektrische Trennung.

Fasernfängerinhalt ca. 3L
Saugsiebmaschenweite ca. 2,2 x 2,2 mm

Material short text

BADU Eco Future, 1~, 1,10 kW

Technical data

Hydraulic power

Flow rate	31 m³/h
Head (min.)	20.3 – 207.002 mWS

Motor & drive

Speed (max.)	600 – 3,000 min-1
Motor phases	1~
Degree of protection	IP 55

Insulation class	F

Electrics

Power input P_1 (max.)	0.03 – 1.4 kW
Power output P_2 (max.)	0.01 – 1.1 kW
Voltage (max.)	1~ 230 V
Frequency	50 Hz

General / Product features

Product range	BADU Premium, BADU Green
Certification	TÜV, Green

Filtration

Lint catcher capacity	3 l

Connections & piping

Connection, inlet / suction side	63 mm
Connection, discharge side	63 mm
Recommended suction line diameter	63 mm
Recommended discharge line diameter	63 mm

Acoustics

Sound pressure level (min.)	35.9 – 65.3 dB[A]

Operating conditions & water

Ambient temperature (min.)	40 ° C
Total salt concentration	5 g/l

Dimensions & logistics

Customs tariff number	84137051

Variants

Article number
2106000038