BADU Top II

Product page https://www.speck-neos.medienreaktor-kunden.de/en/p/badu-top-ii-p53631



Description

Proven long-lasting performance with high flexibility and performance. For medium-sized pools, above-ground pools, or smaller swimming ponds.

Areas of use

Swimming pool water circulation in filter systems, which can be installed a maximum of 3 m above or below the water level.

Version

Close-coupled pump with integrated fiber catcher. Bellows mechanical seal mounted on a plastic impeller hub. The motor or pump shaft does not come into contact with the circulating water. Electrically isolated. Fiber catcher capacity approx. 3 l Suction screen mesh size approx. 3.2 x 2.6 mm

Technical data

Hydraulic power

Flow rate	14 m³/h

Motor & drive

Speed (max.)	2,840 min-1
Motor phases	1~
Degree of protection	IP 55
Insulation class	F

Electrics

Voltage (max.)	1~ 230 V
Frequency	50 Hz
Cable length	3 m

General / Product features

Product range	BADU Allround
Certification	TÜV

Filtration

Lint catcher capacity	3 l

Connections & piping

Connection, inlet / suction side	2 Rp
Connection, discharge side	1 1/2 Rp
Recommended discharge line diameter	50 mm

Operating conditions & water

Ambient temperature (min.)	40 ° C
Total salt concentration	5 g/l

Dimensions & logistics

Customs tariff number	84137051

Variants

Article number	Name	Head (min.)	Power input P_1 (max.)	Power output P_2 (max.)	Recommended suction line diameter
2190128138	BADU Top II/12	15.5 mWS	0.72 kW	0.45 kW	50 mm
2190148138	BADU Top II/14	16.5 mWS	0.97 kW	0.65 kW	63 mm
2190088138	BADU Top II/8	14.5 mWS	0.57 kW	0.3 kW	50 mm