BADU 42

Product page https://www.speck-neos.medienreaktor-kunden.de/en/p/badu-42-p53650



Description

Small jet pump and auxiliary pump in three versions. For bathtubs and smaller whirlpools.

Areas of use

BADU 42/6, BADU 42/9 and BADU 42/12 are the ideal jet pumps for bathtubs and whirlpools.

Technical data

Hydraulic power

Operating pressure max.	2.5 bar

Motor & drive

Speed (max.)	2,840 min-1
Insulation class	F

Electrics

Frequency	50 Hz

Filtration

Strainer basket version	-1

Connections & piping

Connection, inlet / suction side	RP 1 1/2
Connection, discharge side	RP 1 1/2
Recommended suction line diameter	50 mm
Recommended discharge line diameter	50 mm

Operating conditions & water

Ambient temperature (min.)	0 ° C

Total salt concentration	0 g/l

Dimensions & logistics

Customs tariff number	84137051

Variants

Article number	Name	Flow rate	Head (min.)	Motor phases	Power input P_1 (max.)	Power output P_2 (max.)	Voltage (max.)
2042120137	BADU 42/12	0 m³/h	0 mWS	3~	0.95 kW	0.65 kW	3~ Y/Δ 400/230 V
2042120138	BADU 42/12	12 m³/h	0 – 11.5 mWS	1~	0.97 kW	0.65 kW	1~ 230 V
2042060137	BADU 42/6	0 – 9 m³/h	0 mWS	3~	0.55 kW	0.3 kW	3~ Y/Δ 400/230 V
2042060138	BADU 42/6	6 – 9 m³/h	0 – 7.7 mWS	1~	0.58 kW	0.3 kW	1~ 230 V
2042090137	BADU 42/9	0 m³/h	0 mWS	3~	0.68 kW	0.45 kW	3~ Y/Δ 400/230 V
2042090138	BADU 42/9	9 m³/h	0 – 9.1 mWS	1~	0.69 kW	0.45 kW	1~ 230 V