INOVA BN 10

Article number 6511000038
Product page https://www.speck-neos.medienreaktor-kunden.de/en/p/inova-bn-10-6511000038



Description

Die Brauchwasserpumpe mit Gewindeanschlüssen leistet viel bei wenig Stromverbrauch. Absperr- und Rückschlagventil sind in der Pumpe integriert. Diese Pumpe darf nur für Trinkwasser eingesetzt werden.

Areas of use

Drinking water circulation systems

Version

Wet-running circulation pump with screw connection and stall-current-resistant synchronous motor. Low power consumption of only 3 to 4.5 watts thanks to the synchronous motor. Application range up to max. 20° dH. Quick electrical connection via connector. High-quality materials to protect against bacteria and corrosion. Flexible service motor: quick replacement for common pump types. Includes thermal insulation shell. Includes check valve and ball shut-off valve. Pump medium: Drinking water up to 20° dH.

Material short text

Brauchwasserpumpe BN 10 A, We.

Technical data

Hydraulic power

Flow rate	0.4 m³/h
Head (min.)	1 mWS
Operating pressure max.	10 bar

Motor & drive

Speed (max.)	2,850 min-1
Motor phases	1~
Degree of protection	IP 42
Insulation class	F

Electrics

Power input P_1 (max.)	5 kW
Voltage (max.)	1~ 230 V ± 10 %
Input voltage	230 V
Frequency	50 Hz

Connections & piping

Connection, inlet / suction side	R 1/2
Connection, discharge side	G 1

Operating conditions & water

Temperature min.	65 ° C

Dimensions & logistics

Customs tariff number	84137030