SPR-H für 3 Pumpenanlagen

Product page https://www.speck-neos.medienreaktor-kunden.de/en/p/spr-h-fur-3-pumpenanlagen-p53699



Description

Die Frequenzregelung für Ein- und Mehrpumpdruckerhöhungs-Anlagen wird als stahlgekapselter Schaltschrank geliefert und sorgt für eine optimale Anpassungen der Pumpe an die Anwendung.

Areas of use

Water supply Cooling circuit Irrigation Industrial applications

Version

The SPR-H speed controller optimally adapts the pump to the system. The pump controller is available for the following control types: Constant pressure control Temperature control Level control Vacuum control. The SPR-H speed controller is supplied as an IP 54 steel-enclosed control cabinet. The speed controller is equipped with a plain-text display, keypad, main switch, and motor protection. The system is factory-configured. Fuses are provided for each pump, a H-0-A switch for each pump, and a PTC thermistor connection. Special versions Remote control Remote monitoring via GSM module Water meter Pre-feed monitoring/refilling

Technical data

Motor & drive

Motor phases	3~
Degree of protection	IP 54

Electrics

Voltage (max.)	3~ 400 V
Frequency	50 Hz

Operating conditions & water

Ambient temperature (min.)	0 ° C
Temperature min.	0 ° C

Dimensions & logistics

Customs tariff number	85371098

Variants

Article number	Name	Power output P_2 (max.)
5606430203	SPR-H 030-402-P	0.75 kW
5606430402	SPR-H 030-404-P	1.5 kW
5606430602	SPR-H 030-406-P	2.2 kW
5606430701	SPR-H 030-407-P	3 kW
5606430901	SPR-H 030-409-P	4 kW
5606431201	SPR-H 030-412-P	5.5 kW
5606431701	SPR-H 030-417-P	7.5 kW
5606432301	SPR-H 030-423-P	11 kW
5606433201	SPR-H 030-432-P	15 kW
5606433801	SPR-H 030-438-P	18.5 kW
5606434401	SPR-H 030-444-P	22 kW
5606436001	SPR-H 030-460-P	30 kW
5606437501	SPR-H 030-475-P	37 kW
5606439001	SPR-H 030-490-P	45 kW