SPR-VLT

Product page https://www.speck-neos.medienreaktor-kunden.de/en/p/spr-vlt-p53701



Description

Die Frequenzregelung für Einpumpdurckerhöhungs-Anlagen kann direkt an der Wand montiert werden und sorgt für eine optimale Anpassung der Pumpe an die Anwendung.

Areas of use

Water supply Cooling circuit Irrigation Industrial applications

Version

The SPR-VLT speed controller optimally adapts the pump to the system. The pump controller is available for the following control types: Setpoint control External setpoint Fixed setpoint The SPR-VLT speed controller can be mounted directly on the wall. The speed controller is equipped with a plain-text display, PTC thermistor connection, operating mode selector buttons, and a repair switch. The system is factory-configured.

Technical data

Motor & drive

Degree of protection	IP 66

Electrics

Voltage (max.)	3~ 400 V
Frequency	60 Hz

Operating conditions & water

Ambient temperature (min.)	0 ° C
Temperature min.	0 ° C

Dimensions & logistics

Customs tariff number	85371098

Variants

Article number	Name	Motor phases	Power output P_2 (max.)
5606140210	SPR-VLT-402	3~	0.75 kW
5606140310	SPR-VLT-403	3~	1.1 kW
5606140410	SPR-VLT-404	3~	1.5 kW
5606140510	SPR-VLT-405	3~	2.2 kW
5606140710	SPR-VLT-407	3~	3 kW
5606141010	SPR-VLT-410	3 ~	4 kW
5606141310	SPR-VLT-413	3~	5.5 kW
5606141610	SPR-VLT-416	3~	7.5 kW
5606142410	SPR-VLT-424	3~	11 kW
5606143210	SPR-VLT-432	3~	15 kW
5606143710	SPR-VLT-437	3~	18.5 kW
5606144410	SPR-VLT-444	3~	22 kW
5606146110	SPR-VLT-461	3~	30 kW
5606147310	SPR-VLT-473	3~	37 kW
5606149010	SPR-VLT-490	3~	45 kW