TOP 90

Product page https://www.speck-neos.medienreaktor-kunden.de/en/p/top-90-p53713



Description

Optimale Entwässerung durch die Tauchmotorpumpen mit korrosionsbeständigen Materialien von Speck mit sehr flexiblem Einsatz und nicht nur für Wasser einsetzbar.

Areas of use

Basement drainage Drainage of pump shafts Wastewater disposal Rainwater pumping Groundwater pumping

Version

Fully submersible submersible pump made of stainless steel. Motor with built-in thermal overload protection (for AC). Ready to connect with a 10 m cable and Schuko plug (for AC), with a free cable end (for three-phase). AC = AC 1~ 230 V, with floating switch D = Three-phase 3~ 400 V, without floating switch VOX = Open impeller Pump medium: Pure water, wastewater, and dirty water, without long-fiber components.

Technical data

Hydraulic power

Flow rate	24 m³/h
Head (min.)	7.5 mWS

Motor & drive

Speed (max.)	2,850 min-1
Degree of protection	IP 68
Insulation class	F

Electrics

Power output P_2 (max.)	0.55 kW
Frequency	50 Hz
Cable length	10 m

Connections & piping

Connection, discharge side	2 Rp

Dimensions & logistics

Customs tariff number	84137021

Variants

Article number	Name	Motor phases	Power input P_1 (max.)	Voltage (max.)	Energy efficiency class
6422075127	TOP 90 VOX D	3~	0.8 kW	3~ 400 V	IE3
6422075138	TOP 90 VOX WS	1~	0.88 kW	1~ 230 V	IE2