SUPS 46

Product page https://www.speck-neos.medienreaktor-kunden.de/en/p/sups-46-p53723



Description

Die Unterwasserpumpen zeichnen sich durch eine hohe Wirtschaftlichkeit, lange Lebensdauer und einen gekapselten Unterwassermotor aus. Alle medium berührten Teile sind aus Edelstahl.

Areas of use

Water supply. Irrigation. Fountain systems. Heat pumps. Rainwater harvesting

Technical data

Hydraulic power

Flow rate	60 m³/h
Operating pressure max.	25 bar

Motor & drive

Speed (max.)	2,800 min-1
Motor phases	3 ~
Degree of protection	IP 68
Insulation class	B

Electrics

Power input P_1 (max.)	0 kW
Voltage (max.)	3~ 400 V ± 10 %
Frequency	50 Hz

Energy efficiency

Energy efficiency class	IE3

Operating conditions & water

Ambient temperature (min.)	30 ° C

Temperature min.	30 ° C

Dimensions & logistics

Customs tariff number	84137029

Variants

Article number	Name	Head (min.)	Power output P_2 (max.)
5161460017	SUPS 46-1 (3 ~400V)	14 mWS	2.2 kW
5161460107	SUPS 46-10 (3 ~400V)	138 mWS	15 kW
5161460117	SUPS 46-11 (3 ~400V)	151 mWS	18.5 kW
5161460127	SUPS 46-12 (3 ~400V)	165 mWS	18.5 kW
5161460137	SUPS 46-13 (3 ~400V)	179 mWS	22 kW
5161460147	SUPS 46-14 (3 ~400V)	193 mWS	22 kW
5161460157	SUPS 46-15 (3 ~400V)	206 mWS	22 kW
5161460027	SUPS 46-2 (3 ~400V)	28 mWS	3 kW
5161460037	SUPS 46-3 (3 ~400V)	41 mWS	5.5 kW
5161460047	SUPS 46-4 (3 ~400V)	55 mWS	7.5 kW
5161460057	SUPS 46-5 (3 ~400V)	69 mWS	7.5 kW
5161460067	SUPS 46-6 (3 ~400V)	83 mWS	9.3 kW
5161460077	SUPS 46-7 (3 ~400V)	96 mWS	11 kW
5161460087	SUPS 46-8 (3 ~400V)	110 mWS	15 kW
5161460097	SUPS 46-9 (3 ~400V)	124 mWS	15 kW