SUPS 58

Product page https://www.speck-neos.medienreaktor-kunden.de/en/p/sups-58-p53725



Description

Die Unterwasserpumpen zeichnen sich durch eine hohe Wirtschaftlichkeit, lange Lebensdauer und einen gekapselten Unterwassermotor aus. Alle medium berührten Teile sind aus Edelstahl.

Areas of use

Water supply. Irrigation. Fountain systems. Heat pumps. Rainwater harvesting

Technical data

Hydraulic power

Flow rate	77.5 m³/h
Operating pressure max.	25 bar

Motor & drive

Speed (max.)	2,800 min-1
Motor phases	3 ~
Degree of protection	IP 68
Insulation class	B

Electrics

Power input P_1 (max.)	0 kW
Voltage (max.)	3~ 400 V ± 10 %
Frequency	50 Hz

Energy efficiency

Energy efficiency class	IE3

Operating conditions & water

Ambient temperature (min.)	30 ° C

Temperature min.	30 ° C

Dimensions & logistics

Customs tariff number	84137029

Variants

Article number	Name	Head (min.)	Power output P_2 (max.)
5161580017	SUPS 58-1 (3 ~400V)	14 mWS	2.2 kW
5161580107	SUPS 58-10 (3 ~400V)	142 mWS	18.5 kW
5161580117	SUPS 58-11 (3 ~400V)	156 mWS	22 kW
5161580127	SUPS 58-12 (3 ~400V)	170 mWS	22 kW
5161580137	SUPS 58-13 (3 ~400V)	185 mWS	30 kW
5161580147	SUPS 58-14 (3 ~400V)	199 mWS	30 kW
5161580157	SUPS 58-15 (3 ~400V)	213 mWS	30 kW
5161580027	SUPS 58-2 (3 ~400V)	28 mWS	4 kW
5161580037	SUPS 58-3 (3 ~400V)	43 mWS	5.5 kW
5161580047	SUPS 58-4 (3 ~400V)	57 mWS	7.5 kW
5161580057	SUPS 58-5 (3 ~400V)	71 mWS	9.3 kW
5161580067	SUPS 58-6 (3 ~400V)	85 mWS	11 kW
5161580077	SUPS 58-7 (3 ~400V)	99 mWS	15 kW
5161580087	SUPS 58-8 (3 ~400V)	114 mWS	15 kW
5161580097	SUPS 58-9 (3 ~400V)	128 mWS	18.5 kW