# NP10

Product page https://www.speck-neos.medienreaktor-kunden.de/en/p/np10-p53767



## Areas of use

>High-pressure cleaning: They ensure effective high-pressure cleaning. >Air humidification: They ensure even and efficient air humidification. >Fire extinguishing systems: They are used in fire extinguishing systems for safe firefighting. >Sewer cleaning: They support the efficient cleaning of sewers.

## Technical data

### Motor & drive

| | |
|---|---|
| Speed (max.) | 1,450 min-1 |

### Electrics

| | |
|---|---|
| Frequency | 50 Hz |

### Connections & piping

| | |
|---|---|
| Connection, discharge side | 2x G3/8" |

### Operating conditions & water

| | |
|---|---|
| Ambient temperature (min.) | 40 ° C |
| Temperature min. | 70 ° C |

## Dimensions & logistics

| | |
|---|---|
| Customs tariff number | 84135080 |

## Variants

| Article number | Name | Flow rate | Head (min.) | Operating pressure max. | Power input max. | Connection, inlet / suction side |
|---|---|---|---|---|---|---|
| | NP10-1-170 | 1.2 l/min | 1,733.517 mWS | 170 bar | 0.5 kW | 2x G1/2" |
| | NP10-10-150 | 10.6 l/min | 1,529.574 mWS | 150 bar | 3.3 kW | 2x G3/8" / 2x 1/2" |
| | NP10-13-150 | 13.1 l/min | 1,529.574 mWS | 150 bar | 4 kW | 2x G3/8" / 2x 1/2" |
| | NP10-15-150 | 14.6 l/min | 1,529.574 mWS | 150 bar | 4.6 kW | 2x G3/8" / 2x 1/2" |

| Article number | Name | Flow rate | Head (min.) | Operating pressure max. | Power input max. | Connection, inlet / suction side |
|---|---|---|---|---|---|---|
| | NP10-2-170 | 2.3 l/min | 1,733.517 mWS | 170 bar | 1.1 kW | 2x G1/2" |
| | NP10-4-150 | 3.4 l/min | 1,529.574 mWS | 150 bar | 1 kW | 2x G3/8" / 2x 1/2" |
| | NP10-7-150 | 7.2 l/min | 1,529.574 mWS | 150 bar | 2.1 kW | 2x G3/8" / 2x 1/2" |