VI

Product page https://www.speck-neos.medienreaktor-kunden.de/en/p/vi-p53819



Description

Single-stage liquid ring vacuum pumps with an internal water retention system. Their advantages include a water-saving and quiet design, as well as low susceptibility to scaling.

Areas of use

>Boiler feed pumps: These are used for efficient boiler feed pumping. >Condensate pumps: These ensure the effective pumping of condensate.

Technical data

Motor & drive

Speed (max.)	2,850 min-1
Degree of protection	IP 54

Electrics

Frequency	50 Hz

Operating conditions & water

Ambient temperature (min.)	40 ° C

Dimensions & logistics

Customs tariff number	84141089

Variants

Article number	Name	Flow rate	Suction pressure	Power output P_2 (max.)	Energy efficiency class	Connection, inlet / suction side	Connection, discharge side
	VI 2	2.2 m³/h	45 mbar	0.12 kW	IE2	G 1/4"	G 1/4"
	VI 25	24 m³/h	40 mbar	0.75 kW	IE3	G 1/2"	G 1/2"
	VI 30	27 m³/h	33 mbar	1.1 kW	IE3	G 1"	G 1"

Article number	Name	Flow rate	Suction pressure	Power output P_2 (max.)	Energy efficiency class	Connection, inlet / suction side	Connection, discharge side
	VI 55	46 m³/h	33 mbar	1.5 kW	IE3	G 1"	G 1"
	VI 8	9.5 m³/h	40 mbar	0.4 kW	IE2	G 3/8"	G 3/8"