2 VGX 12

Product page https://www.speck-neos.medienreaktor-kunden.de/en/p/2-vgx-12-p53859



Description

Horizontal, single- or two-stage pumps in close-coupled design. They are characterized by a compact design and a long service life. All wetted parts are made of stainless steel.

Areas of use

Water treatment Water supply Cooling systems Apparatus construction

Version

Close-coupled pump with surface-cooled motor, extended motor shaft for the impellers, shaft sealing by a mechanical seal, designed for continuous operation. Fluid: Clear, even moderately aggressive liquids that do not chemically or mechanically attack the pump materials. Special designs: Special voltages: Special elastomers: Special mechanical seals: Higher fluid temperatures:

Technical data

Hydraulic power

Flow rate	9 m³/h

Motor & drive

Speed (max.)	2,850 min-1
Degree of protection	IP 55
Insulation class	F

Electrics

Power input P_1 (max.)	0 kW
Frequency	50 Hz

Dimensions & logistics

Customs tariff number	84137075

Variants

Article number	Name	Head (min.)	Motor phases	Power output P_2 (max.)	Voltage (max.)
6412304137A	2 VGX 12/15	46 mWS	3~	1.1 kW	3~ 230/400 V ± 10 %
6412304138A	2 VGX 12/15	–	1~	1.5 kW	1~ 230 V ± 10 %
6412305137A	2 VGX 12/20	55 mWS	3~	1.5 kW	3~ 230/400 V ± 10 %
6412305138A	VGX 20/20	55 mWS	1~	1.8 kW	1~ 230 V ± 10 %
6412307137A	2 VGX 12/30	63 mWS	3~	2.2 kW	3~ 230/400 V ± 10 %
6412308137A	2 VGX 12/40	72 mWS	3~	3 kW	3~ 230/400 V ± 10 %