2 VGX 20

Product page https://www.speck-neos.medienreaktor-kunden.de/en/p/2-vgx-20-p53860



Description

Horizontal, single- or two-stage pumps in close-coupled design. They are characterized by a compact design and a long service life. All wetted parts are made of stainless steel.

Areas of use

Water treatment Water supply Cooling systems Apparatus construction

Version

Close-coupled pump with surface-cooled motor, extended motor shaft for the impellers, shaft sealing by a mechanical seal, designed for continuous operation. Fluid: Clear, even moderately aggressive liquids that do not chemically or mechanically attack the pump materials. Special designs: Special voltages: Special elastomers: Special mechanical seals: Higher fluid temperatures:

Technical data

Motor & drive

Speed (max.)	2,850 min-1
Motor phases	3~
Degree of protection	IP 55
Insulation class	F

Electrics

Power input P_1 (max.)	0 kW
Voltage (max.)	3~ 230/400 V ± 10 %
Frequency	50 Hz

Dimensions & logistics

Customs tariff number	84137075

Variants

Article number	Name	Head (min.)	Power output P_2 (max.)
6412407137A	2 VGX 20/30	55 mWS	2.2 kW
6412408137A	2 VGX 20/40	66 mWS	3 kW
6412409137A	2 VGX 20/50	75 mWS	3.7 kW